



Sales memo, from Danfoss Heating Controls

2008-09-12

ASV-PV upgrade set

ASV-PV upgrade set is for upgrading ASV-PV with 5 – 25 kPa setting to 20 – 40 kPa setting. Available is for valve sizes DN 15 to DN 40.

Purpose of the set is solution if customer is experiencing too low p setting after ASV-PV 5 – 25 kPa has already been bought and installed. With this upgrade set change to higher setting 20 – 40 kPa is possible.

Introduction + ordering and delivery

ASV-PV upgrade set will soon be available for all DSC's, and can be ordered from Danfoss Silkeborg. It will be ready for order and delivery from week 39.

The product will be available on a request only. It is not supposed to be listed as an accessory in documentation / marketing material available to customers.

Sales information

Text	Code number	PCL	Stat no.	EAN-code singlepack	EAN-code multipack	Pc./mpack
SPRING ASV PV DN15 20-40kPa	003L8246	125	03266	5702421560518	5702421560525	30
SPRING ASV PV DN20 20-40kPa	003L8247	125	03266	5702421560532	5702421560549	30
SPRING ASV PV DN25 20-40kPa	003L8248	125	03266	5702421560556	5702421560563	30
SPRING ASV PV DN32/DN40 20-40kPa	003L8249	125	03266	5702421560570	5702421560587	20

Packaging

All code-numbers are packed as single packed and multipacked. In a single package the following items are included:

- spring,
- upgrade instructions,
- p setting instructions.

Literature

A graphic instruction is being enclosed with the products. The instruction can also be found on the intranet.

Technical support: Matjaž Osojnik, Henrik Blitger